

INDUSTRIAL - SOFT VINYL

Issue date : 12/12/2014

PVC CLEAR 100MIC AP906 PET100

Face Material

Gloss clear polimeric soft vinyl.

Type	Soft vinyl	
Colour and Finish	Gloss clear	
Weight	134 g/m ² ±10%	ISO-536
Thickness	100 µ ±10%	ISO 534-80

Adhesive

Solvent based permanent acrylic adhesive featuring good water and cleaning agents resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	ASP8A permanent	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-30°C/+140°C	
Shear	> 200 H FINAT FTM8	
Initial Adhesion	> 12 N/inch FINAT FTM1	
Final Adhesion	> 15 N/inch FINAT FTM1	
Quantity	40+/-3 gms FTM12	

Liner

Type	One side siliconised polyester	
Colour and Finish	Clear	
Weight	140 g/m ² ±10%	ISO 536
Thickness	100 µ ±10%	ISO 534
Transparency	>90 %	DIN 53 147-64

Applications

For Stone Guard application in the Automotive Industry

Printing Methods

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

